

Application

A non-metallic bow spring centralizer for applications such as soil nails, rock bolts, anchors, sheathing, small diameter drop pipe, down hole cameras, geophysical tools and other data collection devices. Adjustable diameters to fit 0.70" OD up to 2.56" OD and four models to suit numerous ID-OD combinations.

Construction & Features

- Made from ACETAL POM engineering thermoplastic with high flexural strength, high temperature resistance, low co-efficient of friction, abrasion resistance and outstanding chemical resistance.
- Curved and wide bow profile for easy insertion.
- Simple integrated cable tie method of assembly. No special tool required for installation.
- The flexible bows can deflect under force to pass minor obstructions in the borehole.
- Greater diameters are accommodated by joining additional segments.



Models

| Model | Runner (Bow) Height | Part # | Operating Temp (Deg F) | Recommended for use on Pipe/Nail Diameter | Units per carton | Carton Dimensions (L x W x H) | Gross Carton Weight |
|---------|---------------------|--------|---|---|------------------|-------------------------------|---------------------|
| GT 10-1 | 0.39" | 00987 | - 4 F to 176 F (temperatures above 122 F may require closer intervals) | 0.70" OD- 2.56" OD | 100 | 10.43" x 5.51" x 8.27" | 3.19 lbs |
| GT 20-1 | 0.78" | 00989 | | | 100 | 11.34" x 7.25" x 7" | 3.67 lbs |
| GT 30-1 | 1.18" | 00988 | | | 100 | 13.35" x 7.25" x 8.58" | 4.4 lbs |
| GT 40-1 | 1.57" | 00990 | | | 100 | 14.10" x 7.25" x 10.24" | 5.92 lbs |

Compliance

- Manufactured under a certified ISO 9001 Quality Management System.
- Compliant with AS/NZS 4020:2005 Products for use in contact with drinking water.
- Complaint with lead free requirements of Section 1417 of the US Safe Water Drinking Act.

| | |
|---------------|----------------------|
| Notes: | Submitted By: |
|---------------|----------------------|